USSN 10/822,240

Docket No.: 0075-1

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the

application:

Listing of Claims:

1. (cancelled)

2. (currently amended): A utility knife for glaziers and SHEET ROCK (TM) dry wall

users, comprising,

a. a reversible, detachable blade <u>having a flat surface that defines a two-dimensional</u>

plane in space, said blade having a sharp edge and a plurality of anchoring holes;

b. a substantially V-shaped handle for supporting the blade, said handle comprising

a substantially V-shaped left-sidefirst member and a substantially V-shaped right

sidesecond member, wherein said left sidefirst member is removably attached to

said right sidesecond member in order to create said substantially V-shaped

handle, wherein one leg of the V-shape is a gripping portion and the other leg of

the V-shape is a blade supporting portion, and said gripping portion is angulated

with respect to said blade such that said gripping portion is angulated away from

and out of said two-dimensional plane-and-said-blade supporting portion when

viewed from a side view in the plane defined by said blade;

c.locating means-disposed within said blade supporting portion of said handle for

capturing said knife blade;

<u>d.c.</u>channel means disposed within said blade supporting portion of said handle for containing and supporting said blade in a vertical plane;

- d. locating means disposed within said channel means for capturing said blade;
- e. clamping means for clamping said left-first and right-sidesecond members and supporting said knife blade-in a horizontal plane; and
- f. a cavity for holding extra knife blade elements; wherein a user may expose a fresh edge of said blade by either replacing said blade with a new blade from said cavity or by rotating said blade by 180 degrees to change handedness of said utility knife.
- 3. (cancelled)
- 4. (previously presented): A utility knife as recited by claim 2 wherein said angulation ranges from about 100 degrees to about 170 degrees.
- 5. (previously presented): A utility knife as recited by claim 2 wherein said angulation ranges from about 135 degrees to about 150 degrees.
- 6. (cancelled)
- 7. (currently amended): A utility knife as recited in claim 2 wherein said locating means is attached to said right sidesecond member.
- 8. (cancelled)
- (cancelled): A utility knife as recited by claim 2 wherein said channel is milled to a
 width that loosely fits the edges of said knife blade.
- 10. (previously presented): A utility knife as recited by claim 2 wherein said clamping means comprises at least one bolt.

USSN 10/822,240 Docket No.: 0075-1

11. (currently amended): A utility knife as recited by claim 10, wherein said at least one bolt is threaded to the thickness of through said left side first member.

12. (currently amended): A utility knife as recited by claim 10, wherein said at least one bolt is slidably fitted to said right sidesecond member.